



AVANT H30-D.

SE TROUVE DANS CES COULEURS:



BLANC-GRIS (BRILLANT)



SPEED SILVER (MAT)




VERT MILITAIRE-DORÉ (BRILLANT)

SPÉCIFICATIONS ET OPTIONS

CADRE	Orbea Avant Hydro disc, hydroformed triple butted aluminium, HS 1,5" ICR, BB 68mm - BSC English, Thru Axle 12x142mm rear, thread M12x2 P1, Internal Cable Routing, SP 27,2mm, MMS system.
FOURCHE	Orbea carbon fork 2021, aluminum steerer, 1-1/8" head tube
PLATEAU DE PEDALIER	Shimano RS510 34x50t
DIRECTION	Acros Alloy 1-1/2" Internal Cable Routing
CINTRE	OC1 Road, reach 80mm, drop 125mm OC1 Road, riser 15mm, reach 70mm, drop 125mm
POTENCE	OC1 31.8mm interface -6°
MANETTES	Shimano ST-7020
FREINS	Shimano R7070 Hydraulic Disc
PIGNON	Sun Race CSRS3 11-34t 11-Speed
DERAILLEUR ARRIERE	Shimano 105 R7000 GS
DERAILLEUR AVANT	Shimano 105 R7000
CHAINE	Fsa Team Issue
ROUES	Orbea wheel: Cosra with 12mm E-Thru hubset Shimano RS470 28H
PNEUS	Vittoria Zafiro V Rigid bead 700x28c
TIGE SELLE	Alloy 27.2 Offset 20
SELLE	Selle Royal Seta RS Prologo Akero AGX STN size 155mm
GUIDOLINE	Orbea Eva
BLOCAGE AVANT	Orbea Thru Axle 12x100mm M12x2 P1 Solid
BLOCAGE ARRIERE	Orbea Thru Axle 12x142mm M12x2 P1 Solid

GÉOMÉTRIE

TAILLE	47	49	51	53	55	57	60
1 - SEAT_TUBE	420	445	470	495	520	545	575
2 - TOP_TUBE	511	526	539	553	569	586	597
3 - HEAD_TUBE	122	141	161	180	201	221	241
4 - CHAIN_STAY	425						
5 - BB_HEIGHT	264	264	264	266	266	266	266
6 - BB_DROP	75	75	75	73	73	73	73
7 - WHEELBASE	989	996	1004	1006	1020	1029	1038
8 - HEAD_ANGLE	71°	71.5°	71.9°	72.4°	72.6°	72.8°	73°
9 - SEAT_ANGLE	74.5°	74°	73.75°	73.5°	73.5°	73°	73°
10 - STANDOVER	713	738	761	790	809	833	852
11 - REACH	365	370	375	380	390	395	400
12 - STACK	525	545	565	585	605	625	645
13 - FORK_LENGTH	370						
14 - OFFSET	48	48	48	43	43	43	43



ERGONOMIE

TAILLE	BIELLE	POTENCE	CINTRE
47	170	90	380
49	170	100	400
51	170	100	420
53	170	100	420
55	172	110	420
57	172	110	440
60	175	120	440

* La dimension du guidon est centre-centre